



Standard Tracker Model ST-5020-S-A / ST-5020-M-A

Tracker Installation Guide for 3 & 4 Wire units with External Antenna

Installing the Tracker

Unit should be attached to equipment with provided hardware, or another similar method to ensure a secure mounting.

1. Choose a location and attach the tracker. Make sure it will be within reach of the battery connection.
2. Install the antenna with clear access to the sky. Use mounting metal plate if surface is not metal for best cellular reception.
3. Connect the tracker's power wires to the equipment's battery to provide 12 to 24 VDC to SolarTrak. The wire with the fuse holder MUST be attached to the Positive (+) battery terminal. Coil any excess wire loosely.
4. Connect the 3rd and 4th wire to a sensor or device that will show a change in voltage. Example: Ignition circuit (for combustion engines) or the solenoid (for electric motors).
5. Last, connect the tracker to the battery using the gray waterproof connector.

After Installation

A. Tell your company's SolarTrak Administrator which SolarTrak unit (using the unit's serial number) has been installed on which piece of equipment. Tell your administrator the Manufacturer, the Model number, plus any company identifier (like your inventory number).

B. Once installation is completed, the equipment will appear in SolarTrak online in the "Trackers" view as "Unassigned".

C. Once your company's SolarTrak Administrator assigns a specific SolarTrak unit to a specific piece of equipment, the equipment will appear online in the Map View and List View and can be tracked.

BAD INSTALL CHOICES

Do not install on moving parts, or on sides of vehicles without constant access to the sky. These locations will prevent the GPS from working correctly.

USER GUIDE: [www.solar_trak/Downloads/USER GUIDE](http://www.solar_trak/Downloads/USER%20GUIDE)

Tracker Info:

Tracker

3rd & 4th
Wire

Battery
Connector
Cable

Screw Mount Antenna

Drill a hole and install antenna with unobstructed view of the sky for best satellite reception, then tighten nut to secure.



Magnetic Antenna

Simply attach with clear view to the sky - no hole needed.



Sample 3rd & 4th Wire Installation



Run 3rd Wire (blue) along back of battery drawer and connect with ring terminal



 **SOLARTECH**®

Any questions? Call SolarTrak Support: **484-223-4994**

7620 Cetronia Rd, Allentown, PA
Rev 062025